

Approval Certificate



This is to certify, that the undernoted products have been approved in accordance with the relevant requirements of the GL Approval System.

Certificate No. **94 612 - 10 HH**

Company **Frenzelit-Werke GmbH & Co. KG**

Frankenhammer 7
95460 Bad Berneck, GERMANY

Product **PTFE based Flat Gasket**
(structured and modified PTFE, filled with functional fillers)

Type **novafalon 100, 200, 300, 500**

Technical Data / Application	Technical Data	100	200	300	500
	Material				
	Density (DIN 28090-2) - g/cm ³	1,7	2,9	2,1	0,9
	Compressibility (F36) - %	25	3	5	50
	Recovery (ASTM F36J) - %	40	45	45	10
	Residual stress 30MPa@150°C (DIN 52913)- N/mm ²	12	14	16	18
	Cold compressibility (DIN 28090-2) - %	20	3	3	40
	Hot creep 20MPa@150°C (DIN 28090-2) - %	45	40	20	15
	Tightness (DIN 3535-6) - mg/(sxm)	<0,015	<0,015	<0,015	<0,015

Dimensions (mm) : 1500 x 1500
Thickness (mm) : 1,5, 2,0, 3,0

Application
Refer to page 2.

Approval Standard **DIN 86076:2007, ASTM F36, DIN 52910, DIN 3535-6, DIN 28090**

Documents

- Test report dated 26.04.2010 DIN 52913, DVGW test reports acc. to DIN 3535-6, Quality control reports according to standards referenced.
- Audit report
- Technical data sheets


Remarks **None**


Valid until **2015-06-15**

File No. **XI.B.03**

Germanischer Lloyd

Hamburg, 2010-06-16


Hanspeter Raschle


Hagen Markus

Approval Certificate



Certificate No. 94 612 - 10 HH

Application

- Ship's piping systems including cargo lines on Chemical and Gas Tankers carrying propylene oxide and mixtures of ethylene / propylene oxide.
- Maximum allowable working pressure and temperature according to the specification of the manufacturer.

The selection of the gasket material for the corresponding service, the storage and the right installation are to be according to the manufacturers instruction.

Germanischer Lloyd

Hamburg, 2010-06-16

i. V. Hansp. Raschle *Hagen Markus*

Hanspeter Raschle

Hagen Markus